

FLEXI 1000/400



Milner
INDUSTRIAL



More Info?
Call: 01675 475173

Q X 9?8K<\$##" ##YTccbcetg\be
' bhagaZ bagf & ' phaaXfi X[V_XTaWj \UX
Wk\XeWj \j T; baW cXgb_XaZ'aX!

Q X 9?8K<\$##" ##[TfT \$###\gxiTVhh` gTa^TaW
T" ##\gX \eXf[j Tgkegfa^Za UTft.gZei`
cb\Xgd\XaX!Q X WTe^Vb.bheXVhVXf`g X\be Tgba
bYT_ZTX`WhX`p HI zV[g`5bg`gTa^fT`e`Vb` c_Xg\`
fXcT`e`g`Wfi fg\` f`fb`g`T`gYfXVT`_ bYghe`TaWb\`
VTaabgVbagf` aTg`g`X`eXf[j Tgkefhcc\!Q X`
X` cg j XZ[gY`ba\`&+#^Z!`8`Xa j \j T`&Z` phaaXf`
i X[V_X\`bhj \`abgUX`bi XebTWKW

Q X` bpeTaWch` c T`e`agXZ`e`g`W`a`p`g`X`
' TV[\aX!Q X`bcgbat_\`vbi Xec`d`g`V`g`f`i bheha`g`
TZT`afgUT`Wj XT`g`XeVbaW`g`baf!Q X`vbi XeT`fb`f`T`
cXeXVgl`i`YU_X`c`I`VX`bel bheTW`Xeg`faZ`" XffTZ`Xf!

Q X`eT` X`TaWiTVhh` gTa^T`e`Vb` c_Xg\`
[bgWc`Z`T`i`Ta`fXWUbg` \afVW`TaWbh`g`e`fh`gaZ`
'a`UX`g`Xec`Xeb`e` TaVX`TaWT`a`Va`e`T`fXW`_X`fc`Ta`bY`
g`X`" TV[\aX!

Lightweight and compact, without compromising quality. This is why our FLEXI is appreciated worldwide. With high quality and functionality, the FLEXI combines durability, ease of use and reliability you need being a toilet service specialist. This all to ensure your emptying and cleaning more cabins a day in a comfortable way. Because cleaning more cabins means making more profit!

- Why a Flexi?**
- Profitable price-quality ratio
 - Over 30 years of experience
 - Durable & Reliable & Safe
 - Ease of use
 - Wide choice
 - Directly available from stock
 - Maintenance friendly
 - Professional after sales
 - Easy ordering through online parts catalogue
 - Manuals in Dutch, English, German and French

STANDARD

- Lightweight (from just 380kg) for more loading capacity (toilet cabins and fresh / vacuum water etc.)
- Compact measurements (maximal space for toilet cabins)
- ✓ Produced according to high quality and safety standards (CE-mark)
- 1** Gasoline engine Honda GX 270 QME, electric- and handstart, including charging current switch
- 2** Solid construction with thermically galvanised frame and tank (outside and inside), produced by certified welders
- 3** Spacious vacuum tank: 1000 l.
- 4** Fresh water tank (PE): 1 x 400 l. The basalt grey colour reduces the formation of algae due to UV-light.
- 5** Vacuum pump (2.500 l/min.), sprayed in silver metallic anticorrosion paint, incl. automatic oil lubrication
- Sub frame on anti-vibration mounts for smooth running of motor-/pump combination
- 6** Combined oil separator/muffler
 - Integrated galvanised fork lift tubes, enabling easy (dis)mounting of your unit onto/off your vehicle
- 7** All safety measures required, such as an emergency stop, over pressure and under pressure safety valves
- ✓ Double safety valve (prevents over-suctioning)
- ✓ Moisture separator, incl. second ball valve (protects vacuum pump by discharging moisture that comes along with air. Second ball valve is an extra safety to prevent over- suctioning)
- ✓ Partial protection of the components of your machine
- 8** Level indicator and pressure gauge on vacuum tank
- 9** Inspection cover with air vent
- 10** Robust Hi-Vac toilet vacuum hose, equipped with suction pipe and ball valve incl. storage system

Standard = delivered with machine

✓ = safety

OPTIONAL

- Longer suction hose, 15.2m instead of 9.1m
- Drain hose (ND 75 x 2.4m)
- 1** Integrated cover for optimal protection of the components of your machine
- Level indicator fresh water tank
- HP cleaning installation 100 bar - 14 l/min: HP pump, incl. spraygun with double lance
- 2** Low pressure water pump 40 l/min, incl. 18m ND 13 hose on auto-retracting hose reel
- Active carbon filter element for air filtration and noise reduction (stainless steel housing and filter element)
- Additional oil reservoir for RV2500 vacuum pump
- Drain valve moisture separator and oil separator
- Installation on flat cargofloor
- Bodywork package; Load platforms, incl. cyclist protection bars for unit and 4 toilet cabins, incl. accessories
- Unit fitted with coupling for drain hose (3" Camlock) for British market

Optional = at surcharge

✓ = safety

