

STANDARD

- Lightweight (from just 380kg) for more loading capacity (toilet cabins and fresh / vacuum water etc.)
- Compact measurements (maximal space for toilet cabins)
- ✓ Produced according to high quality and safety standards (CE-mark)
- 1** Gasoline engine Honda GX 270 QME, electric- and handstart, including charging current switch
- 2** Solid construction with thermically galvanised frame and tank (outside and inside), produced by certified welders
- 3** Spacious vacuum tank: 1000 l.
- 4** Fresh water tank (PE): 1 x 400 l. The basalt grey colour reduces the formation of algae due to UV-light.
- 5** Vacuum pump (2.500 l/min.), sprayed in silver metallic anticorrosion paint, incl. automatic oil lubrication
- Sub frame on anti-vibration mounts for smooth running of motor-/pump combination
- 6** Combined oil separator/muffler
 - Integrated galvanised fork lift tubes, enabling easy (dis)mounting of your unit onto/off your vehicle
- 7** All safety measures required, such as an emergency stop, over pressure and under pressure safety valves
- ✓ Double safety valve (prevents over-suctioning)
- ✓ Moisture separator, incl. second ball valve (protects vacuum pump by discharging moisture that comes along with air. Second ball valve is an extra safety to prevent over-suctioning)
- ✓ Partial protection of the components of your machine
- 8** Level indicator and pressure gauge on vacuum tank
- 9** Inspection cover with air vent
- 10** Robust Hi-Vac toilet vacuum hose, equipped with suction pipe and ball valve incl. storage system

Standard = delivered with machine

✓ = safety

OPTIONAL

- Longer suction hose, 15.2m instead of 9.1m
- Drain hose (ND 75 x 2.4m)
- 1** Integrated cover for optimal protection of the components of your machine
- Level indicator fresh water tank
- HP cleaning installation 100 bar - 14 l/min: HP pump, incl. spraygun with double lance
- 2** Low pressure water pump 40 l/min, incl. 18m ND 13 hose on auto-retracting hose reel
- Active carbon filter element for air filtration and noise reduction (stainless steel housing and filter element)
- Additional oil reservoir for RV2500 vacuum pump
- Drain valve moisture separator and oil separator
- Installation on flat cargofloor
- Bodywork package; Load platforms, incl. cyclist protection bars for unit and 4 toilet cabins, incl. accessories
- Unit fitted with coupling for drain hose (3" Camlock) for British market

Optional = at surcharge

✓ = safety

