



# ROM 1600

## VACUUM TRAILER

The ROM 1600 vacuum trailer is suitable for suction works, such as the emptying of flooded basements or garages.

The ROM 1600 trailer guarantees you efficient and effective deployment of your machine. ROM offers you a maximum of mobility and flexibility.

Multi storey car parks, for example, are easy to access. Some advantages:

- Compact design; Ideal for areas which are difficult to access, for example car parks.
- All components are placed at an ergonomic height and are easy to reach.
- The ROM 1600 has been designed according to a durable concept, where attention was devoted to both functionality and design of the machine.
- Manually operated hydraulic driven tipping system.

### TYPICAL ROM 1600 CHARACTERISTICS

#### SAFETY

The vacuum system consists of a floating ball valve in the tank (over suction protection), moisture trap with sight glass, vacuum valve (set to  $\pm 0.65$  bar) and combined oil separator/exhaust silencer. This ensures you can work safely.

#### USER FRIENDLY

The ROM 1600 is a user friendly machine. All components are placed at an ergonomic height and are easy to reach. Furthermore, the vacuum tank can be tipped hydraulically by using the hand pump.

#### DURABLE


The vacuum tank is robust and very durable because it has been completely galvanised.

### OPTIONS

- 13hp Kubota Z482 diesel engine instead of petrol engine.
- Heavy-Duty vacuum pump, model VacuStar L 400, 325m<sup>3</sup>/h (instead of standard vacuum pump).
- Digital speed/working hour counter for petrol engine.
- Working light on magnetic bracket.
- Working light on pole.
- Rotating beacon on pole.
- Vacuum hose reel, excluding vacuum hose.
- 18m. vacuum hose 2", suction pipe with ball valve (in combination with option 0654).
- Second connection with 18m. vacuum hose 2", suction pipe with ball valve. Two hooks for vacuum hose storage and holster for suction pipe.
- Sampling connection ND75.
- Drain pipe for discharging water, halfway of the sludge water tank level.
- 2,5m. 3" vacuum hose with Perrot coupling.
- 3" suction pipe of aluminium, complete with handle and 3" valve in storage holder.
- Protection mat for inside the toolbox (price per metre).
- Vacuum tank spray painted in special colour for unit (RAL).
- Active carbon filter element for air filtration and noise reduction, consisting of stainless steel housing and filter element.
- RDW vehicle approval test (Only NL) < 3500kg.

## THE ROM 1600 IS AVAILABLE IN THE FOLLOWING VERSION:

Article number	0307
Name	ROM 1600 Vacuum trailer (twin axle)
Engine	13,2kW / 18pk B&S VANGUARD Petrol engine
Vacuum pump	MEC 4000
Capacity	4350 l/min
Tank capacity	1600l
Empty weight (excl. options)	approx. 1350kg
Vacuum hose	ND70 x 2,5m (2 pieces)
Dimensions (L x W x H)	4750 + 1810 + 1840mm



### OPTIONS

- 13hp Kubota Z482 diesel engine instead of petrol engine.
- Heavy-Duty vacuum pump, model VacuStar L 400, 325m<sup>3</sup>/h (instead of standard vacuum pump).
- Digital speed/working hour counter for petrol engine.
- Working light on magnetic bracket.
- Working light on pole.
- Rotating beacon on pole.
- Vacuum hose reel, excluding vacuum hose.
- 18m. vacuum hose 2", suction pipe with ball valve (in combination with option 0654).
- Second connection with 18m. vacuum hose 2", suction pipe with ball valve. Two hooks for vacuum hose storage and holster for suction pipe.
- Sampling connection ND75.
- Drain pipe for discharging water, halfway of the sludge water tank level.
- 2,5m. 3" vacuum hose with Perrot coupling.
- 3" suction pipe of aluminium, complete with handle and 3" valve in storage holder.
- Protection mat for inside the toolbox (price per metre).
- Vacuum tank spray painted in special colour for unit (RAL).
- Active carbon filter element for air filtration and noise reduction, consisting of stainless steel housing and filter element.
- RDW vehicle approval test (Only NL) < 3500kg.

